

Indian Register of Shipping

Report No.:

SURVEY REPORT FOR INITIAL/PERIODICAL/RENEWAL/CHANGE OF FLAG/ GENERAL EXAMINATION * OF PASSENGER SHIP /CARGO SHIP SAFETY RADIO EQUIPMENT* UNDER GMDSS

(Under the provisions of the SOLAS 1974 as amended, for passenger ships irrespective of size, and cargo ships of 300 tons gross tonnage and over)

Name o	or snip			IMO Number			
Port of	Registry			Gross Tonnage			
Flag				Date Keel Laid			
First da	ate of survey	:		Last date of surv	ey:		
Signal	letters and i	dentification codes:					
Call sig	gn:			ID for DSC (VHF)	·		
Selcall	No. for NBD	P:		ID for DSC (MF/H	(F):		
1st ID f	or INMARS	AT-B/ Fleet 77:		ID for DSC (MF):.			
2 nd ID for INMARSAT- B/ Fleet 77: 1 st ID for INMARSAT-C:							
ID for S	Satellite EPII	RB:		2 nd ID for INMAR	SART-C:		
		rvey to be marked "Y" (Yes)	, ,				
Note 2:	Functional t	ests are to be verified for com	pliance wi	th IMO performance	standard.		
Can ama	o in which w	essal is contified to amounts. A	1 🗆	A 2 🗔 - A 1 - A 2 - A 2 [¬. ∧1,∧2,	A2+A4□ (Daa I	(/ 10)
		essel is certified to operate: A		A2 □; A1+A2+A3 □	_; A1+A2+	-A3+A4 □ (Reg. I	V 12)
Any ou	ner specific a	rea:	•••••				Ш
1. DOC	CUMENTAT	TION					
1.1	Valid radio	license issued by flag admini	stration ava	ailable on board			
1.2	Verification	of radio operators certificate					
		Name	Rank	Certificate Held	Expiry	Issued by	
1st Ope							
2 nd Ope							
3 rd Ope		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1					
1.3		et the chin's compliment com			Jannina Da		
1.4		at the ship's compliment com at the master, officers and rat	_				
1.6		of radio log	ings are ce	itilied as required by	the STCW	Convention	
1.7		that up to date International	Telecomm	unication Convention	(ITU) publ	ication are	
1.8		that operating manuals are a	vailable, or	n board for all equipn	nent		
1.9		that service manuals are avai				naintenance is the	•••
1.10	Confirmation that a Radio record (logbook) has been kent in the period since last survey to the				•••		
Verification whether any new equipment has been fitted and, if so, confirmation that it has been approved to appropriate performance standards prior installation and that any changes are reflected in the appropriate certificate/ record.							
1.12	GMDS, is o	n board, (Reference			.dated)	
1.13	GMDS, is on board, (Reference						•••

1.14 Checking documentary evidence that the actual capacity of the battery has been proved in port within the last 12 months
--

2. SELECTED METHOD OF MAINTENANCE

Duplication of equipment	•••
Shore-based maintenance	
At –sea maintenance	

3. GENERAL CHECKING OF RADIO INSTALLATION

3.1	Are all radio controls for operating the radio installation adequately illuminated	
3.2	Are ships call sign, ship station identity, and other codes, as applicable, for use of the radio station posted	
3.3	Is the radio installation protected from adverse environmental conditions	
3.4	Is the radio installation so located that no harmful interference affects its use and so located to ensure the greatest possibility of operational availability.	
3.5	General examination of all antennas (including INMARSAT antennas) including insulation and safety	
3.6	Are spare parts and tools available	
3.7	For at-sea maintenance are additional technical documentation, tools, measuring equipment and spare parts available.	
3.8	Facilities for bridge wings communications	
3.9	Verification of the equipment fitted in accordance with Form R (Supplement to Cargo Ship Safety Radio Certificate)/ Form P (Supplement to Passenger Ship Safety Certificate)	
3.10	Verification that all two way communication equipment capable of automatically including ship's position in the distress alert are continuously and automatically provided with the information from internal or external navigation receiver. If such receiver is not on board, verification of procedure for manually updating the position and the time of determining the position at intervals not exceeding 4 hours.	

4. SOURCES OF ENERGY

4.1	Main	•••	Emergency	•••	Reserve	•••
4.2			e of energy has sufficier 6 hours as appropriate		operate the primary or the	
4.3	If the reserve source o specific gravity measu			e appropriate,	of its good condition by	
4.4	If the reserve source o battery within 10 hour		attery, verification that t	he chargers ar	re capable of re-charging the	
4.5			e maximum required rac ery voltage and dischar		load connected to the reserve	

5. COMPOSITION OF RADIO INSTALLATION

	VHF	MF	MF/HF	INMARSAT
Primary System	•••	•••	•••	•••
Duplicated System	•••	•••	•••	

6. V.H.F RADIO INSTALLATION

6.1	Checking for operation on channel 6, 13 and 16	
6.2	Checking proper operation of all controls including priority of control units	
6.3	Checking the operation of the VHF control unit(s) or portable VHF equipment provided for navigational safety	
6.4	Checking for correct operation by on-air contact with a coast station or other ship	
6.5	Checking for correct transmission and reception by means of a routine or test call to a coast station, other ship, onboard duplicate equipment or special test equipment	
6.6	Examining Channel 70 DSC watch receiver, including confirmation that correct Maritime Mobile Service Identity (MMSI) is programmed in the equipment, and verification of DSC alarm	
6.7	Checking for operation from main, emergency (if fitted), and reserve source of energy	

7. MF/HF* RADIO TELEPHONE INSTALLATION

7.1	General examination of MF/HF* Radio telephone equipment	
7.2	Verification that equipment operates from main, emergency (if provided) and reserve source of energy	
7.3	Checking the MF/HF* Radio telephone equipment for correct operation by contacting a coast station and/or measuring transmission quality and radio frequency output	•••
7.3.1	During the survey	
a)	Is the DSC equipment tested in Routine call category with the ship station and or a shore station.	
b)	Is the DSC equipment tested in Safety call category with a ship station and or a shore station.	
c)	Confirming that the correct Maritime Mobile Service Identity is programmed in the equipment.	
d)	Checking the off-air self-test program.	
7.4	Verification of antenna tuning in all appropriate bands.	
7.5	Checking that control unit on bridge has first priority for purposes of initiating distress alerts, if control units are provided outside the navigation bridge.	
7.6	Checking receiver performance by monitoring known radio station on all appropriate bands.	
7.7	Verification that the correct selective calling number is programmed in the equipment.	
7.8	Verification of availability of the MF/HF* DSC alarm.	
7.9	Verification that only distress and safety DSC frequencies are being monitored on the MF/HF* DSC watch receiver	

8. INMARSAT SHIP EARTH STATION

Note: Ship earth station (other than Inmarsat-C) which forms part of the GMDSS must conform to the Performance Standard as follows:

- 1. If designed to operate in a mobile satellite service recognized on or after 1 January 2021, complies with the relevant requirements of resolution A.1001 (25) and conforms to performance standards not inferior to those specified in the Annex to Resolution MSC.434 (98).
- 2. If designed to operate in a mobile satellite service recognized before 1 January 2021:
 - a. Conforms to the relevant requirements of resolution A.1001 (25) and conforms to performance standards not inferior to those specified in the Annex to Resolution MSC.434 (98). OR
 - b. Conforms to the performance standards not inferior to those specified in the annex to:
 - i. Resolution MSC.130 (75) on Performance standards for Inmarsat Ship Earth Stations capable of two-way communications, if installed after 1 February 1999.
 - ii. Resolution A.808(19) on Performance standards for Ship Earth Stations capable of two-way communications, if installed on or after 23 November 1996 and before 1 February 1999;
 - iii. Resolution A.698 (17) on Performance standards for Ship Earth Stations capable of two-way communications, if installed before 23 November 1996.

8.1	Verification that equipment operates from main, emergency (if provided) and reserve source of energy	
8.2	Verification of distress function by means of an approved test procedure, where possible	
8.3	Verification of correct operation by inspection of recent hard copy of test call by telex or telephone.	

9. NAVTEX RECEIVER

Note: NAVTEX receiver equipment installed on or after 1 July 2019 must conforms to performance standards not inferior to those set out in the annex to resolution A.148 (77), as amended by the annex to resolution MSC.430 (98).

9.1	Verification for correct operation by monitoring incoming message or inspecting recent hard copy/display unit	
9.2	Performance test run of the self test program if provided	

10. ENHANCED GROUP CALL (EGC)

Note: EGC equipment installed on or after 1 July 2019 must conforms to performance standards not inferior to those set out in the annex to resolution MSC.306 (87), as amended by the annex to resolution MSC.431 (98).

10.1	Verification for correct operation and area by monitoring incoming messages or by inspecting recent hard copy.	•••
10.2	Performance test run of the self test programs, if provided.	

11. HF-NBDP EQUIPMENT (applicable if ship exempted from INMARSAT EGC receiver)

11.1	Checking for correct operation by monitoring incoming messages or by inspecting recent hard copy	
11.2	Performance test run of the self test programs, if provided.	

12. TWO WAY RADIO TELEPHONE APPARATUS

12.1	Examination of two way VHF radio apparatus including verification of its correct operation on both channel 16 and any other channel through a test with another fixed or portable VHF installation.				•••
12.2	2.2 Expiry of Primary Battery 1. 2. 3.				
12.3	Charging arrangement for battery, where rechargeable battery is used				

13. EPIRB

	VHF EPIRB		406 MHz EPIRB		•••	
13.1	Verification of condition by visual	examination, po	sition and mounting fo	r float fre	e operation	
13.2	Self test routine					
13.3	Labeling of EPIRB					
13.3.1	Verification of battery expiry date	1		2		
13.3.2	Manufacturer's serial number					
13.3.3	Verification that call sign of the sh	ip marked on the	EPIRB			
13.4	Verification of hydrostatic release date	and its expiry	1		2	
Additio	onally for 406 MHz EPIRB					
13.5	Verification of emission on operati without transmission of a distress of			on on the	406 MHz signal	
13.6	Annual Testing of the satellite EPIRB carried out on:					
13.7	Date system last replaced or Shore based maintenance carried out (not exceeding 5 years)					
13.8	Verification that EPIRB ID is clear	ly marked on the	e outside of the equipn	nent	_	

14. SECONDARY MEANS OF ALERTING

Designated equipment				
VHF (DSC)		INMARSAT B/Fleet 77	 INMARSAT –C	
MF (DSC)		HF (DSC)	 406 MHz EPIRB	
VHF EPIRB	•••			

15. RADIO LIFE SAVING APPLIANCES

15.1	Operational test of Survival craft radar transponder/ AIS SART*			
15.2	Battery expiry date	1	2	

16. AUTOMATIC IDENTIFICATION SYSTEM

16.1	Operational test carried out	 l
10.1	o peratronal test earlies out	

17. SHIP SECURITY ALERT SYSTEM

17.1	Functionality test carried out with competent authority		
------	---	--	--

18. VOYAGE DATA RECORDER/ SIMPLIFIED VOYAGE DATA RECORDER

18.1	Operational test carried out		l
------	------------------------------	--	---

19. LONG RANGE IDENTIFICATION AND TRACKING:

19.1	Conformance Test Certificate is available on board		
19.2	DNID member number registered by CSP in the LRIT shipborne equipment (i.e. Sat C) is not disabled		
	or deleted	•••	

20. ON PASSENGER SHIPS ONLY:

20.1	Two way on-scene radio communication on 121.5 MHz and 123.1 MHz from navigating bridge.	
20.2	A GOC Certified operator assigned to perform only radio communication duties during distress incidents.	

21. GMDSS RADIO OPERATORS:

21.1	Is the Ship operator(s) able to use the GMDSS equipment and carry out function tests for transmitting and receiving distress and safety alerts	
21.2	Is ship's operators able to explain correct procedures for the followings:	
21.2.1	Canceling a false distress alert (Res.A.814(19))	•••
21.2.2	Receiving a distress alert.	•••
21.2.3	Sending a distress alert	

22. HAS THE VESSEL BEEN EXEMPTED BY THE ADMINISTRATION FROM MEETING THE REQUIREMENTS OF THE CONVENTION

22.1	Administration
22.2	Reference No
22.3	Details

23. ADDITIONAL REQUIREMENTS FOR SHIPS OPERATING IN POLAR WATERS

23.1	For ships intended to operate in low air temperature, checking the certificates or equivalent documents of the systems and equipment required by this Code for the consistence of the polar service temperature specified for the ship (Polar Code part I-A/Ch. 1.4.2) (for Initial Survey)	
23.2	For ships operating in low air temperature, checking the certificates or equivalent documents of the survival systems and equipment for the consistence of the maximum expected rescue time at polar service temperature (Polar Code part I-A/Ch. 1.4.3) (for Initial Survey)	
23.3	Examining, where applicable, the alternative design and arrangements for ship structure, machinery installations, fire safety/protection or life-saving appliances and arrangements, in accordance with the test and inspection requirements, if any, specified in the approved documentation and PWOM (SOLAS 74/00/14 regulation XIV/4) (for Initial Survey)	•••
23.4	Checking that the Polar Water Operational Manual (PWOM) with the hazards identified in the operational assessment being addressed properly is placed on board (Polar Code part I-A/Ch. 2.3, 4.3.1.3 and 4.3.1.4) (for Initial Survey)	
23.5	Confirming that procedures are provided on board for availability of the mandatory communication equipment for use in survival craft, including availability of battery power for the maximum expected time of rescue (Polar Code part I-A/Ch. 10.3.2.3) (for Initial Survey)	
23.6	Confirming that, where applicable, the approved documentation for the alternative design and arrangement is on board, with the relevant contents being entered in PWOM (SOLAS 74/00/14 regulation XIV/4) (for Initial Survey)	
23.7	Confirming the provision of the operational assessment and reviewing any changes thereof (Polar Code part I-A/Ch. 1.5)	
23.8	Confirming that the PWOM is on board, and checking it if any changes occurred since last survey (Polar Code part I-A/Ch. 2.3, 4.3.1.3 and 4.3.1.4)	
23.9	Confirming that procedures are provided on board for availability of the mandatory communication equipment for use in survival craft, including availability of battery power for the maximum expected time of rescue (Polar Code part I-A/Ch. 10.3.2.3)	
23.10	Confirming that the Voyage Plan has been provided on board for the voyages in polar waters since last survey, otherwise if no trading in polar waters, random checking to the historical plans may be considered (Polar Code part I-A/Ch. 11.3)	
23.11	Where applicable, checking the qualifications of the masters, chief mates, officers and/or other persons in charge of a navigational watch on board ships operating in polar waters in accordance with chapter V of the STCW Convention and the STCW Code (Polar Code part I-A/Ch. 12.3.1 and 12.3.2)	
23.12	Checking the qualification certificates (if required by the Administration) and/or familiarization records of all the crew members for their assigned duties referenced in the PWOM (Polar Code part I-A/Ch. 12.3.4)	

Report No.:

23.13	Confirming that, where applicable, the approved documentation for the alternative design and arrangements is on board, with the relevant contents being entered in PWOM (SOLAS 74/00/14 regulation XIV/4)	
23.14	Examining and testing the communication equipment on board for ship-to-ship and ship-to-shore communication, taking into account the limitations of communications systems in high latitudes and the anticipated low temperature (Polar Code part I-A/Ch. 10.3.1.1)	•••
23.15	For ships intended to provide icebreaking escort, examining and testing the sound signalling system capable to be mounted to face astern (Polar Code part I-A/Ch. 10.3.1.2)	•••
23.16	Examining and testing the means for two-way on-scene and SAR coordination communications for search and rescue purposes including aeronautical frequencies operations and that communication equipment provides for two-way voice and data communication with a Telemedical Assistance Service (TMAS) (Polar Code part I-A/Ch. 10.3.1.3 and 10.3.1.4)	
23.17	For ships intended to operate in low air temperature, examining that each rescue boat and lifeboat is capable to be provided with devices for transmitting signals for distress alerting, locating and on-scene communications (Polar Code part I-A/Ch. 10.3.2.1)	
23.18	For ships intended to operate in low air temperature, examining the capabilities of all other survival craft, for transmitting signals for location and for communication (Polar Code part I-A/Ch. 10.3.2.2)	
23.19	Examining, where applicable, the alternative design and arrangements for life-saving appliances and arrangements, in accordance with the test, inspection and maintenance requirements, if any, specified in the approved documentation and PWOM (SOLAS 74/00/14 regulation XIV/4)	
23.20	Confirmation that Polar Ship Certificate has been issued/ endorsed* based on satisfactory survey	•••

34. REMARKS

Name of Surveyor:	Name of Radio Inspector:
Signature of Surveyor:	Signature of Radio Inspector:
	Radio Company:
Official Seal	Official Seal
T	
Date:	
Port:	
Port:	