CLASS ANNUAL SURVEY/INTERMEDIATE SURVEY/SPECIAL SURVEY/ **GENERAL EXAMINATION* CHECKLIST FOR BULK CARRIER**

Ship Name: I.R. No.:

Report No.:

Notes:

1. Refer BWM statutory checklist for items related to BWM survey when class & statutory survey for BWM carried out concurrently.

DOCUMENTATION

APPROVED TRIM & STABILITY INFORMATION

Confirmation of availability of trim and stability booklet approved by administration.

FIRE CONTROL PLANS

Verification of proper posting of fire control plans. (including duplicate sets permanently stored in a prominently marked weather tight enclosures outside deckhouse)

LOADING MANUAL

Verified that vessel has an approved Loading Manual.

LOADING INSTRUMENT

Availability of an approved loading instrument together with its operational manual & verification of test cases.

STEERING GEAR ENTRIES REOUIRED BY SOLAS/FLAG

Verification of entries made in the ship's log for departure Steering checks & Emergency Steering drills.

DAMAGE STABILITY

Availability of damage stability information.

(Note: Applicable for Cargo vessel of 80 m & above length on or after 01/07/1998 and length > 100 m on or after 01/02/1992)

ESP DOCUMENT

Availability of ESP documents on board. Survey report file is to be part of the documentation consisting of reports of structural survey, executing hull summary, thickness measurement reports. Additional supporting documentation to be available on board include, main structural plans of cargo holds and ballast tanks, previous repair history, cargo and ballast history, inspection by ship's personnel with reference to structural deterioration in general, leakages in bulkheads and piping, condition of coating or corrosion prevention system if any, any other information that will help identify critical structural areas and/or suspect areas requiring inspection, survey programme.

(Note: For CSR ships structural plans are to include for each structural element both the as-built and renewal thickness. Any thickness for voluntary addition is also to be clearly indicated on the plans. The midship section plan to be supplied on board the ship is to include the minimum allowable hull girder sectional properties for hold transverse section in all cargo holds)

STATUTORY CERTIFICATES

Valid Statutory certificates available on board.

DAMAGE CONTROL PLANS & BOOKLET

Verification that damage control plans and booklet are available

(Note: Applicable for vessels of 500 GT & over and constructed on or after 01/02/1992)

MANOEUVRING BOOKLET

Confirmation that the manoeuvring booklet is on board and the manoeuring information is displayed on the navigation bridge.

CARGO SECURING MANUAL

Confirmation of availability of approved cargo securing manual.

THE SHIP STRUCTURE ACCESS MANUAL

Confirming that the Ship Structure Access Manual is on board (bulk carriers of 20,000GT and over, constructed on or after 1st Jan. 2006)

CONSTRUCTION DRAWINGS MAINTAINED ON BOARD

Confirmation that structural alterations performed, if any, have been approved by the classification society and reported on the as-built drawings kept on board.

(Note: Applicable for ship constructed on or after 1st Jan. 2007)

Condition to be reported using number code as follows:

- 1. When examined found to be satisfactory and/or examined/tested satisfactory and/or confirmed arrangements exist in satisfactory condition. No repairs considered necessary this time.
- Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or confirmed arrangements exist in satisfactory condition.
- Repairs now recommended and remain outstanding.

4. Opportunity to examine/test was not provided this time. Remains outstanding.

LOADING/UNLOADING BOOKLET

a. Confirming, that the loading/unloading booklet required in SOLAS regulation VI/7 is on board.

b. Confirming that; where restrictions are imposed with respect to the carriage of cargoes with a density of 1,780 kg/m3 and above,

- 1. the restrictions imposed are identified and recorded in the booklet and;
- 2. a triangle is permanently marked at midship.

EMERGENCY TOWING PROCEDURES

Confirmation that ship specific emergency towing procedures available on board.

COATING TECHNICAL FILE

Confirmation that Coating Technical File is available on board and maintained.

(Note: Applicable for ships of not less than 500 gross tonnage provided with dedicated seawater ballast tanks and double-side skin spaces arranged for ships of 150 m in length and upwards for which the building contract is placed on or after 01/07/2008 or the keels of which are laid on or after 01/01/2009 or which are delivered on or after 01/07/2012.

OWNER'S INSPECTION AND MAINTENANCE OF CARGO HATCH COVERS

Confirmation that vessel is provided with maintenance plan for cargo hatch covers and coamings and record maintained for the inspection, maintenance and replacement of components.

SHIP CONSTRUCTION FILE (SCF)

Confirming availability of Ship Construction File. Examining the ship's structure in accordance with the Ship Construction File, taking into account, identified areas that need special attention.

A – For the SCF stored on board ship, the Surveyor is to examine the information on board ship. In cases where any major event, including, but not limited to, substantial repair and conversion, or any modification to the ship structures, the surveyor is to also verify that the updated information is kept on board the ship. If the updating of the SCF onboard is not completed at the time of survey, the Surveyor is to record it and request for confirmation at the next periodical survey.

 \mathbf{B} – For the SCF stored on shore archive, the Surveyor is to examine the list of information included on shore archive. In cases where any major event, including, but not limited to, substantial repair and conversion, or any modification to the ship structures, the Surveyor is to also verify that the updated information is stored on shore archive by examining the list of information included on shore archive or kept on board the ship. In addition, the Surveyor is to confirm that the service contract with the Archive Center is valid. If the updating of the SCF Supplement ashore is not completed at the time of survey, the Surveyor is to record it and request for confirmation at the next periodical survey.

(Note: Applicable for bulk carrier of 150 m length & above as per SOLAS Chapter II-1, Part A-1, Regulation 3-10 (built to Goal Based Standards))

HARMONIC DISTORTION RECORD FOR VESSEL FITTED WITH HARMONIC FILTER.

Verification of annual measurement record of harmonic distortion level at bus bar (Applicable for vessel keel laid before 1 July 2017 and for any modification on electrical distribution system on existing vessel, total distortion measured along with equipment running at the time of measurement to be recorded)

OPERATIONAL MANUAL FOR EFFECT OF HARMONIC FILTER

Verification that following document are available on board.

- 1) Effect of failure on harmonic filter on electrical distribution system.
- 2) Permitted modes of operation for maintaining harmonic distortion level within acceptable limit during normal operation and during failure of filter.
- 3) Approved copy of relaxation on allowable distortion limit, if any
- 4) Record of harmonic distortion level measured.

(Note: Applicable for vessel keel laid on or after 01 July 2017 and on exiting ship retrofitted with harmonic filter on or after 01 July 2017.)

ALTERNATIVE DESIGN AND ARRANGEMENTS

Confirmation that, where applicable, the approved documentation for the alternative design and arrangements is on board.

PROCEDURAL REQUIREMENT FOR CERTAIN ESP SURVEYS

Confirmation that procedural requirement in respect of conduct of intermediate and special surveys by two exclusive surveyors complied with for following cases:

On ships 20,000 tonnes DWT and above, subject to ESP, starting with special survey No.3, all special and intermediate hull classification surveys are to be carried out by at least two exclusive surveyors.

On bulk carriers 100,000 dwt and above of single side skin construction the intermediate hull classification survey

Condition to be reported using number code as follows:

- 1. When examined found to be satisfactory and/or examined/tested satisfactory and/or confirmed arrangements exist in satisfactory condition. No repairs considered necessary this time.
- 2. Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or confirmed arrangements exist in satisfactory condition.
- . Repairs now recommended and remain outstanding.
- 4. Opportunity to examine/test was not provided this time. Remains outstanding.

between 10 and 15 years of age is to be performed by two exclusive surveyors.

For dual class vessels where this requirement of two surveyors (where compatible with relevant laws and regulations) was fulfilled by having one surveyor from each society, name of the other society surveyor is to be provided in "Remarks section"

HULL AND WEATHER DECK FIRE DOORS AND CONTROLS a. Examination of manual/automatic fire doors, verification of their satisfactory operation and confirmation that no holding back arrangements exist and arrangements for self-closing & locking are in order. b. Confirmation that fire doors provided between machinery space and steering gear compartment are of gastight, self-closing type and without any hold back arrangements. (Note: applicable where emergency fire pump is in steering gear compartment) **ANCHORING & MOORING EQUIPMENT** Examining the anchoring equipment & mooring equipment. At renewal survey, during the examination, anchors are lowered and raised using the windlass. SOUNDING PIPES Sounding pipes, including self closing devices on short sounding pipes. HATCHWAYS Examination and testing of hatchways (Access hatch) on freeboard and superstructure decks including efficient condition of closing appliances, side bow and stern doors, flush deck scuttles, ash shoots and other openings. WEATHER DECKS Examination of weather decks, ships side plating above water line. HULL MARKINGS Verification that hull markings such as freeboard markings, draft markings, vessel name, IMO number, port of registry are legible and in satisfactory condition. VENTILATORS Examination and or testing of ventilators including efficiency of their closing appliances. WINDOWS, SIDE SCUTTLES AND DEAD LIGHTS Examination and or testing of windows, side scuttles and dead lights. SCUPPERS, SANITARY DISCHARGES, VALVES AND CONTROLS Examination scuppers and sanitary discharges and valves together with valves and their control gear. SKYLIGHTS AND FIDDLEY OPENINGS Examination and or testing of skylights and fiddley openings including their closing appliances. EXPOSED CASINGS, DECK HOUSES, COMPANION WAYS AND SUPERSTRUCTURES Examination and/testing of exposed casings, deck houses, companionways and superstructure bulkheads including closing appliances. **GUARD RAILS AND/OR BULWARKS** Examination of the condition and arrangement, fittings & appliances for timber deck cargo. **COLLISION & WT BULKHEAD OPENINGS** Examining the collision and the other watertight bulkheads as far as can be seen. Watertight bulkheads penetrations examination as far as practicable for satisfactory condition, watertight doors in watertight bulkheads. MASTS AND STANDING RIGGING Masts, Derricks & Crane columns including their standing rigging. WATER TIGHT DOORS AND CONTROLS Examining and testing (locally and remotely) all the watertight doors in watertight bulkheads including indicating lights and alarms. **COMPANIONWAYS** Verification of Companionways and posting of appropriate notices. CLOSEUP/OVERALL EXAMINATION OF CARGO HATCH COVERS AND COAMINGS Cargo hatch covers and coamings including their closing appliances, stowage, fit including efficiency of closing in sealed condition & operation including hatch cover sets within the forward 25% of the ship's length and atleast one additional set, such that all sets on the ship are assessed at least once in every 5-year period, are to be surveyed open, closed and in operation to the full extent on each direction at each annual survey to the extent as per the requirement Condition to be reported using number code as follows: When examined found to be satisfactory and/or examined/tested satisfactory and/or confirmed arrangements exist in satisfactory condition. No 1. repairs considered necessary this time. Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or

- Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or confirmed arrangements exist in satisfactory condition.
- . Repairs now recommended and remain outstanding.
- 4. Opportunity to examine/test was not provided this time. Remains outstanding.

IRS Rules Part 1 Ch.2, Cl.2.2.2 to 2.2.2.7. Drainage channels and non return valves for cargo hatch to be specially examined. Above mentioned examination carried out for cargo hatch covers for Hold nos (1,2,3,4,5,...etc)/all. TIGHTNESS TESTING OF CLOSING APPLIANCES Where tightness testing of closing appliances such as hatches, doors, etc. is carried out with ultrasonic equipment, confirmation that firm engaged in tightness testing is approved. Name of the firm:..... IRS approval certificate Number...... Validity..... THICKNESS MEASUREMENT Where thickness measurements on structure/plating of the vessel is carried out, confirmation that firm engaged in thickness measurement on vessel is approved. Name of the firm:..... IRS approval certificate Number......Validity..... **REMOTE INSPECTION TECHNIQUES (RIT)** Where remote inspection techniques are used in survey, confirmation that firm engaged for RIT is approved. Name of the firm:.... IRS approval certificate Number......Validity..... NON-DESTRUCTIVE TESTING (NDT) Where NDT carried out onboard, confirmation that the firm providing NDT services is approved. Name of the firm:..... Approval certificate Number...... Issuing Authority...... Validity..... AIR PIPES Examination and or testing of air pipes including efficiency of their closing appliances, weld connection between Air pipes and deck plating. Confirmation that vents from bunker tanks and ballast tanks (with cathodic protection) are equipped with flame screens and mesh provided are in satisfactory condition. **FREEING PORTS** Examination of the condition and arrangement including shutters and crew protection bars. MAINTENANCE, REPAIR AND PARTIAL COATING OF DEDICATED BALLAST TANKS Confirmation that maintenance, repair and partial recoating of dedicated ballast tanks and double side skin spaces, as appropriate, are recorded in the coating technical file and the maintenance of the protective coating is included in the overall ship's maintenance scheme. NEW INSTALLATION OF MATERIALS CONTAINING ASBESTOS Confirming that new equipment containing asbestos was not fitted on board since last survey. ACCESS TO AND WITHIN SPACES IN, AND FORWARD OF, THE CARGO AREA OF OIL TANKERS AND BULK CARRIERS Checking, when appropriate, the provision of means of access to cargo and other spaces in accordance with the arrangements in the Ship Structures Access Manual of bulk carriers of 20,000 G/T and over. Confirming, when appropriate and as far as is practicable when examining internal spaces on bulk carriers of 20,000 G/T and over, that the means of access to cargo and other spaces remain in good condition. GANGWAY, LIFELINES AND MEANS OF EMBARKATION/DISEMBARKATION a. Satisfactory examination of items pertaining to lifelines, accommodation ladder, gangways, Davits, Winches for their satisfactory condition. Verification of inspection and maintenance records. b. Confirmation that embarkation ladder and accommodation ladder including safety net are in satisfactory condition and marked with safe working load. **INTERNAL SPACES** Verification of the permanent means of access where appropriate of the internal spaces as far as practicable. **UPGRADATIONREPAIR TO COATING** Confirmation that maintenance, repair and partial recoating had been done as per manufacturer's specification using acceptable coating system, suitable surface preparation and adequate film thickness under the supervision of coating manufacturer's representative/coating inspector. These had been verified through stage/patrol inspection during survey and considered acceptable. (Note: Ballast tank for which coating condition was upgraded to "GOOD" this time during survey are to be listed in the "Remark" section.) Condition to be reported using number code as follows: When examined found to be satisfactory and/or examined/tested satisfactory and/or confirmed arrangements exist in satisfactory condition. No 1. repairs considered necessary this time. Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or confirmed arrangements exist in satisfactory condition. 3. Repairs now recommended and remain outstanding. 4. Opportunity to examine/test was not provided this time. Remains outstanding. NA- Not Applicable.

WATERTIGHT CABLE TRANSIT SEAL SYSTEMS

(Note: Applicable for all vessels contracted for construction on or after 1st July 2021)

i) Review of the cable transit seal systems register to confirm that it being maintained.

ii) Confirmation that where any disruption to the cable transits or installation of new cable transits carried out onboard from last annual survey, records are reviewed for the satisfactory condition of those transits.

(Note: If deemed necessary examination of such transits to be undertaken)

iii) Examination of cable transits as far as practicable for their satisfactory condition.

iv) Confirmation that the results of survey are recorded in the cable transit seal system register.

v) Where the cable transits have been examined by an approved service supplier, review of the cable transit seal system register to confirm that it has been properly maintained by the owner and correctly endorsed by the service supplier.

OXYGEN AND GAS DETECTION EQUIPMENTS

Confirmation that, when transporting a bulk cargo which is liable to emit a toxic or flammable gas, or cause oxygen depletion in the cargo space, an appropriate instrument for measuring the concentration of gas or oxygen in the air is provided. Verification that instructions for use of such equipment incl. operation by crew are available.

ADDITIONAL REQUIREMENTS:

Additional Annual survey requirements for the foremost cargo hold subject to SOLAS XII/9.

(Note: Overall/close up survey of foremost cargo hold, shell frames, suspect areas including thickness measurement are to be undertaken as required by Rules for vessels subject to SOLAS XII/9).

VESSEL AGE OVER 10 YEARS

CARGO HOLDS:

Single skin/other Bulk carrier: close up survey of forward cargo hold and overall survey of all cargo holds. Double skin bulk carrier: Overall survey of two selected cargo holds. Examination of all piping and penetrations in cargo holds including overboard piping.

VESSEL AGE ABOVE 15 YEARS

CARGO HOLDS:

Overall survey of all cargo holds, close-up examination of a selected cargo hold in addition to the forward cargo hold. All piping and penetrations in cargo holds, including overboard piping are to be examined.

MACHINERY SPACES

MACHINERY AND BOILER SPACES

Confirming that the machinery, boilers and other pressure vessels, associated piping systems and fittings are installed and protected so as to reduce to a minimum any danger to persons on board, due regard being given to moving parts, hot surfaces and other hazards.

FIRE/EXPLOSION HAZARDS

- a. i) Propulsion system and auxiliary machinery, boilers, all pressurized systems (steam, pneumatic, hydraulic) and their associated fittings were examined to see whether they are being properly maintained and with particular attention to the fire and explosion hazards
 - ii)Verification that oil/water leakages, accumulation of oil, with potential source of ignition does not exist in the machinery spaces. Leakages if any have been dealt and source of leakages rectified.

iii) Confirmation that floor plates & gratings are secured and found to be in order.

b. Confirmation that lagging material on hot surfaces, anti-splash tapes on joints are in place as required and highpressure fuel lines are jacketed and spray shields flanged/screwed joints of pipes are in satisfactory condition.

c. Confirmation that arrangement for high pressure fuel oil leak off alarm for propulsion engine, auxiliary engines or any other diesel engines are satisfactory and operational. Drain lines are connected to alarm unit and working satisfactory.

d. Where flexible hoses/pipes are used, examination of hoses/pipes for any signs of material cracking or deterioration to ensure that, there is no damage, cut, kinked, crushed, twisted, hardened, cracked hoses/pipes exists in the oil systems.

e. Confirmation that the supports and retaining devices of low-pressure fuel system provides adequate restraint and are in satisfactory condition.

STEERING GEAR

a. All main and auxiliary steering arrangements and their associated equipment and control systems were examined and tested. Confirmation that various alarms required for hydraulic power operated, electric and electro-hydraulic

Condition to be reported using number code as follows:

- 1. When examined found to be satisfactory and/or examined/tested satisfactory and/or confirmed arrangements exist in satisfactory condition. No repairs considered necessary this time.
- 2. Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or confirmed arrangements exist in satisfactory condition.
- B. Repairs now recommended and remain outstanding.
- 4. Opportunity to examine/test was not provided this time. Remains outstanding.

steering gears are, operating satisfactorily and that the recharging arrangements for hydraulic power operated steering gears are being maintained. Log entries made in accordance with statutory requirements were verified where applicable.

b. Confirmation that steering gear compartment is in satisfactory condition and provided with handrail arrangements, grating or non-slip surface.

MEANS OF COMMUNICATION

All means of communication between the navigating bridge and the machinery control positions including engine room telegraph, as well as the bridge and the main/alternative steering position, if fitted, are tested. Where ships having emergency steering positions there are means of relaying heading information and, when appropriate, supplying visual compass readings to the emergency steering positions. Confirmation that means of indicating the angular position of the rudder are operational.

BOILERS AND PRESSURE VESSELS

Periodical Surveys of boilers and other pressure vessels have been carried out as required by the Rules and the safety devices have been tested. External visual examination. External examination of boilers including test of safety & protective devices and test of safety valve using it's relieving gear. For exhaust gas economizers, review of engine log book to verify that Chief Engineer has tested the safety valves at sea within the window period of Annual Survey.

REMOTE CONTROLS

Examining the means for the operation of the main and auxiliary machinery essential for propulsion and the safety of the ship, including when applicable, the means of remotely controlling the propulsion machinery from the navigating bridge (including the control, monitoring, reporting, alert and safety actions) and the arrangements to operate the main and other machinery from a machinery control room.

BILGE PUMPING ARRANGEMENT

Examination of the bilge pumping systems and bilge wells including operation of each bilge pump (including hand pumps and eductors), extended spindles and level alarms, where fitted. Operational confirmation of emergency bilge suction and bilge-pumping system for each watertight compartment and drainage from enclosed cargo spaces situated on freeboard deck.

Examination and testing of bilge well audible and visual alarms to all cargo holds and conveyor tunnels as applicable for their satisfactory functionality.

For ships complying with the requirements of SOLAS XII/12 for hold, ballast and dry space water level detectors, an examination and a test, at random, of the water ingress detection systems and of their alarms.

CARGO HOLD WATER LEVEL DETECTOR

For Single Hold Cargo Ship examining the cargo hold water level detector and its Audible & Visual alarm.

DANGEROUS GOODS ARRANGEMENTS

Examining, when appropriate, the special arrangements for carrying dangerous goods, including checking the electrical equipment and wiring, the ventilation, the provision of protective clothing and portable appliances and the testing of the water supply, bilge pumping and any water spray system.

FIRST START ARRANGEMENT

Operational confirmation of the means provided to bring the machinery into operation from the dead ship condition without external aid.

NORMAL OPERATION OF PROPULSION MACHINERY

Confirming that the normal operation of the propulsion machinery can be sustained or restored even though one of the essential auxiliaries becomes inoperative.

AUTOMATION

General Examination of automation equipment and examination, testing of the general emergency alarm system. Operation of safety devices, bilge level detection and alarm systems and control systems. Operational confirmation of the engineer's alarm that it is clearly audible in the engineer's accommodation.

SCHEDULE OF BATTERIES

Endorsed schedule of batteries for essential and emergency services available on board and maintenance being done as per this schedule.

Confirm that changes (If any) in battery type, location and rating are reviewed and endorsed.

FORWARD SPACE/TANK BILGE PUMPING SYSTEMS

Examination and test of the pumping systems for draining and pumping ballast tanks forward of the collision bulkhead and bilges of dry spaces any part of which extends forward of the foremost cargo hold and of their controls.

Condition to be reported using number code as follows:

- 1. When examined found to be satisfactory and/or examined/tested satisfactory and/or confirmed arrangements exist in satisfactory condition. No repairs considered necessary this time.
- 2. Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or confirmed arrangements exist in satisfactory condition.
- B. Repairs now recommended and remain outstanding.
- 4. Opportunity to examine/test was not provided this time. Remains outstanding.

SEA WATER PIPE EXPANSION JOINTS

Examining visually the condition of any expansion joints in sea water system.

MACHINERY SPACE VENTILLATION

Confirmation that machinery space ventilation is in good working condition.

EMERGENCY GENERATOR ROOM VENTILATORS ARRANGEMENT

Verification that following requirement of emergency generator room ventilation louvers and its closing appliance examined/tested and found satisfactory.

- a) Manual or power operation of louvers and its closing appliance.
- b) Operating instruction, where hand -operated system is in use
- c) Automatic opening of ventilation louvers whenever emergency generator starting/in operation for power operated system where provided including fail to open operation..
- d) Manual closing operation from outside the space, where open/closed indication clearly marked.

(Note: Applicable for vessel keel laid on or after 01 January 2017)

TOWING AND MOORING EQUIPMENT

Confirming that the towing and mooring equipment is properly marked with any restriction associated with its safe operation for ships constructed on or after 01/01/2007.

MACHINERY VERIFICATION RUNS

Towards completion of Special/Continuous Survey of Machinery, trial of main & auxiliary machinery including the steering gear & controls carried out to confirm satisfactory operation (In afloat condition).

SEA TRIAL

In case of major repairs to main propulsion machinery or steering gear, confirmation that a sea trial has been carried out satisfactorily to confirm proper operation of the relevant machinery in all respects.

(Note: With effect from 1st July 2018, in case of major repairs to main propulsion machinery or steering gear, the scope of sea trial is to also include a test plan for astern response characteristics based on those required for such an equipment or system when fitted to the new ship. The tests are to be carried out at least over the manoeuvring range of the propulsion system and from all control positions. A test plan is to be provided by the manufacturer and accepted by the surveyor. If specific operational characteristics have been defined by the manufacturer, same is to be included in the test plan and the reversing characteristics of the propulsion plant, including the blade pitch control system of controllable pitch propellers, are to be demonstrated and recorded during trials.)

ELECTRICAL INSTALLATION

ELECTRICAL SYSTEM

a. General examination visually and in operation, as feasible, of the main electrical machinery, the emergency sources of electrical power, the switch gear, other electrical equipment including the lighting system. The precautions provided against shock, fire and other hazards of electrical origin for proper maintenance.

b. Confirmation that light covers including emergency lights are in satisfactory condition.

c. Confirmation that 440 V/220 V panels are not showing low insulation resistance.

d. Confirmation that insulation mat is provided around the electrical switch board, panels.

e. Confirmation that the generator breakers, interlocks and generator automatic starting as applicable are in satisfactory operational condition.

f. verification of insulation monitoring devices for all distribution systems. Operation of power management system, where fitted.

EMERGENCY SOURCE OF POWER

The peration of the emergency source(s) of electrical power, including their starting arrangement, the systems supplied, and when appropriate, their automatic operation as far as practicable.

(Note: This to remain independent from the battery source provided for propulsion and/ or main source of power in case battery systems used as main or an additional source of power for propulsion.)

NAVIGATIONAL LIGHT SYSTEM

Verification of Navigational light systems for satisfactory operation of lights, audio-visual indications and power supply arrangement for their satisfactory condition.

MONITORING OF HARMONIC DISTORTATION

Confirmation that equipment for continuous monitoring of harmonic distortion level is in good order, alarm tested, logging of measured value verified in engine log book or electronically in case where automation system fitted and found to satisfactory.

Condition to be reported using number code as follows:

- 1. When examined found to be satisfactory and/or examined/tested satisfactory and/or confirmed arrangements exist in satisfactory condition. No repairs considered necessary this time.
- 2. Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or confirmed arrangements exist in satisfactory condition.
- . Repairs now recommended and remain outstanding.
- 4. Opportunity to examine/test was not provided this time. Remains outstanding.

(Note: Applicable for vessel keel laid on or after 01 July 2017 and on exiting ship retrofitted with harmonic filter on or after 01 July 2017.)

PROTECTION ARRANGEMENT FOR HARMONIC FILTER

Confirmation that protection for harmonic filter, including alarm tested and found satisfactory.

(Note: Applicable for vessel keel laid on or after 01 July 2017 and on exiting ship retrofitted with harmonic filter on or after 01 July 2017.)

MOTOR CONTROLS

Confirmation that motor controls including remote control are in satisfactory operational condition, where provided.

ELECTRICAL PROPULSION

Examination of installation, arrangement of electric motors used for propulsion system, including associated cabling, drives, cooling systems (where provided) is to be carried out. Verification of operational and maintenance logs. Confirmation that controls, alarms, indications including remote control system is in satisfactory operational condition.

ADDITIONAL REQUIREMENTS FOR BATTERY PROP NOTATION

DOCUMENTATION AND RECORDS

Confirmation that batteries are type tested as per relevant IEC standard.

Type of battery used: Nickel Cadmium Battery/Lithium-Ion Battery/ Lead Acid Battery/Nickel Metal Hydride Battery*.

Verification that operation and maintenance manual for Battery Management System (BMS) & Power Management System (PMS) is available along with all the required details of batteries such as battery chemistry, test certificates, cell voltages, system voltages, number of battery banks, recommended charge and discharge rates, functional test, monitoring, software maintenance and other environmental requirements as applicable.

Confirmation that battery manufacturer recommended practices for safety have been documented and implemented satisfactorily.

Confirmation that details of schedule as well as records & log towards storage, maintenance, replacement of batteries is available and maintained.

Confirmation from the records that state of health and state of charge of battery system is maintained satisfactorily.

Confirmation that risk assessment towards possible potential hazards associated with type of battery chemistry, system design and its incorporation is available.

Confirmation from the records that the software updates including verification or testing after updates are being carried out.

SYSTEM ARRANGEMENT AND TESTING

Examination of arrangement for battery installation, battery spaces and equipment as far as practicable for satisfactory condition.

Confirmation of satisfactory operational testing of battery room//spaces ventilation systems and cooling systems as applicable.

Examination of firefighting systems in battery spaces.

Testing of all smoke, gas and fire detectors for their satisfactory condition.

Verification of all emergency shutdown arrangements to confirm their satisfactory operation.

Verification of operation of UPS for their satisfactory performance.

Verification and testing of safety systems arrangements towards overcharging, undercharging, high temperature, gas leakage etc. for satisfactory condition.

Testing of audio-visual alarms and controls for system power supply failure, cell temperature high, battery space high temperature, cell voltage etc.

ADDITIONAL REQUIREMENTS FOR PERFORMANCE MANAGEMENT SYSTEM

Confirmation that arrangement of performance management system including associated cabling, sensors and interconnections maintained as per approved plan.

Verification that on loss of hardware, functions of the systems does not get affected.

(Applicable where the system is provided with dedicated operator stations and servers)

Confirmation from the records that hardware & software inventory maintained and changes if any, have been verified and found in order.

Condition to be reported using number code as follows:

- 1. When examined found to be satisfactory and/or examined/tested satisfactory and/or confirmed arrangements exist in satisfactory condition. No repairs considered necessary this time.
- 2. Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or confirmed arrangements exist in satisfactory condition.
- 3. Repairs now recommended and remain outstanding.
- 4. Opportunity to examine/test was not provided this time. Remains outstanding.

ADDITIONAL REQUIREMENTS FOR SHIPS USING BIO-FUEL BLEND AS FUEL							
Confirmation of following towards use of bio-fuel blend onboard as fuel oil:							
a.	Availability of documented permission from the Flag Administration for use of bio-fuel blend.						
b.	Vessel is in possession of required documents issued by the bunker suppliers to show that the bio-fuel blend meets the relevant specification requirements including Test analysis report as per ISO 8217:2017, BDN, Safety Data Sheet, Proof of Sustainability (PoS) for Biofuels).						
c.	The percentage of bio-fuel in the fuel oil blend supplied to the ship is clearly reflected in the bunker delivery note and that the blend proportion conforms to the limit permitted by Flag Administration.						
d.	Measures are in place in respect of shelf life of the bio-fuel blend used onboard as declared by the bunker supplier.						
e.	Ship specific risk analysis for use of bio-fuel blend is available. Any redundancy requirements onboard as per risk analysis is taken care for the operational safety and emergency contingency measures.						
	Note: Bio-fuel blend is not to be used for emergency equipment e.g. emergency generator, emergency fire pump, etc.						
f.							
g.	g. Shipboard operational procedures for use/ handling of bio-fuel blend including procedures for procurement, availability test result, storage of biofuel blend, frequency of cleaning of fuel filters, inspection of storage tanks, monitoring of transfer lines and associated piping & fittings and any other requirements specified by the manufacturers of engines/equipment is available.						
h.	Crew members onboard are familiarized with the shipboard procedures regarding the handling and use of bio-fuel blend including contingency measures and records are maintained.						
i.	. Maintenance and inspection of fuel oil system including storage tanks, filters, fuel transfer hoses and connectors is undertaken as specified in the shipboard operational procedure and records maintained.						
j.	j. Logging/ monitoring of all relevant engine parameters, maintenance and checks as specified by the manufacturer is undertaken and records maintained.						
ADDITIONAL REQUIREMNETS FOR IMPRESSED CURRENT CATHODIC PROTECTION (ICCP) SYSTEMS							
 DOCUMENTATION AND RECORDS 1. Confirmation that ICCP Manual is available onboard and attachments details of anodes and reference electrodes along with specification of connecting cables are available for reference. 2. Confirmation that record of system operation is maintained and downtime if any is recorded. Confirmation that all 							
anode current outputs and potentials monitored are similar to those settled during previous assessment.3. Confirmation from records that ICCP system is maintained and adjusted by the supplier on regular basis as per manufacturer's instructions.							
SYSTEM OPERATION							
Confirmation that system is in operation and working satisfactory. Confirmation that operation of indicators and control							
on the panel including auto/manual switch are found to be satisfactory.							
PROTECTION ARRANGEMENT FOR ANODE CABLES Confirmation that protection arrangement for ICCP anode cables is in satisfactory condition.							
ALTERNATIVE DESIGN AND ARRANGEMENT							
Where applicable, examination of alternative design and arrangements for machinery or electrical installations, low-flashpoint fuel storage and distribution systems, or fire safety, in accordance with the test inspection and maintenance requirements if any approximation is to be carried out.							
requirements, if any, specified in the approved documentation is to be carried out. FIREFIGHTING/PROTECTION ARRANGEMENTS							
SER	SERVICING OF FIREFIGHTING APPLIANCES						
Verification of evidences for proper maintenance and servicing of firefighting appliances.							
No	•	Item	Inspection Type	Date Last Done			
1		Breathing apparatus	Examination				
2		Portable/Semi portable Fire Extinguishers	Testing Examination				
2		Portable/Semi-portable Fire Extinguishers	Testing				
Condition to be reported using number code as follows:							
rep	repairs considered necessary this time.						
	2. Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or confirmed arrangements exist in satisfactory condition.						

Repairs now recommended and remain outstanding.
 Opportunity to examine/test was not provided this time. Remains outstanding.
 NA- Not Applicable.

3	Fixed Fire Extinguishing System (CO ₂ /Halon/Foam/DCP/Other* (specify))					
	CO ₂	Weighment				
		5 Yearly servicing				
		10 Yearly servicing				
		Testing				
		Examination				
	Halon	Container Content Verified				
		Servicing				
		Container Pressure Testing				
		Examination				
	Foam	Sample Testing				
		Examination				
	DCP	Testing				
		Examination				
	Other (Specify)	Testing				
		Examination				
4	Fireman's outfit	Examination				
5	International Shore Coupling	Examination				
tanko . Coni satis Testo TREM	firmation that emergency fire pump including factory condition and pump is building required ed pressure :bar AINS, HYDRANTS, HOSES, NOZZLES AND APP on of fire main (no soft patches or doublers)	g prime mover and priming water pressure and two jets of v LICATORS together with flanges and val-	arrangements, gauges are vater simultaneously.			
tanko tanko o. Coni satis Testo FIREMA Condition pplicat READIN Each ho	ers). firmation that emergency fire pump including factory condition and pump is building required ed pressure :bar AINS, HYDRANTS, HOSES, NOZZLES AND APP on of fire main (no soft patches or doublers) tors, spanners, relief valves and international sho NESS OF FIRE HYDRANTS, HOSES ose complete with couplings, nozzle (dual-purpos	g prime mover and priming water pressure and two jets of v LICATORS together with flanges and val- re connection.	arrangements, gauges are water simultaneously. ves, hydrants, hoses, nozz			
tanko c. Con satis Testa FIREM/ Condition pplicat READIN Each ho PORTA Confirm hat who	ers). firmation that emergency fire pump including factory condition and pump is building required ed pressure :bar AINS, HYDRANTS, HOSES, NOZZLES AND APP on of fire main (no soft patches or doublers) tors, spanners, relief valves and international sho NESS OF FIRE HYDRANTS, HOSES ose complete with couplings, nozzle (dual-purpos BLE EXTINGUISHERS AND FOAM APPLICATO nation that portable fire extinguishers correspond en examined were in good condition, fully charge	g prime mover and priming water pressure and two jets of v LICATORS together with flanges and val- re connection. we nozzles where applicable) and DRS 1 to the fire control plan w.r.t.	arrangements, gauges are water simultaneously. ves, hydrants, hoses, nozz d tools kept ready for use.			
tanka c. Com satis Testo FIREMA Condition PORTA Confirm hat who SPARE	ers). firmation that emergency fire pump including factory condition and pump is building required ed pressure :bar AINS, HYDRANTS, HOSES, NOZZLES AND APP on of fire main (no soft patches or doublers) tors, spanners, relief valves and international sho NESS OF FIRE HYDRANTS, HOSES ose complete with couplings, nozzle (dual-purpos BLE EXTINGUISHERS AND FOAM APPLICATO nation that portable fire extinguishers correspond en examined were in good condition, fully charge CHARGES	g prime mover and priming water pressure and two jets of w LICATORS together with flanges and value re connection. The nozzles where applicable) and ORS d to the fire control plan w.r.t. re ed and ready for use.	arrangements, gauges are water simultaneously. ves, hydrants, hoses, nozz d tools kept ready for use. number, type and location a			
tanka c. Con: satis Testo FIREMA Condition PORTA Confirm hat who SPARE Availab	ers). firmation that emergency fire pump including factory condition and pump is building required ed pressure :bar AINS, HYDRANTS, HOSES, NOZZLES AND APP on of fire main (no soft patches or doublers) tors, spanners, relief valves and international sho NESS OF FIRE HYDRANTS, HOSES ose complete with couplings, nozzle (dual-purpos BLE EXTINGUISHERS AND FOAM APPLICATC nation that portable fire extinguishers correspond en examined were in good condition, fully charge CHARGES bility of spare charge/s for each portable extinguistic	g prime mover and priming water pressure and two jets of w LICATORS together with flanges and value re connection. The nozzles where applicable) and ORS d to the fire control plan w.r.t. re ed and ready for use.	arrangements, gauges are water simultaneously. ves, hydrants, hoses, nozz d tools kept ready for use. number, type and location a			
tanka tanka Conditional condit	ers). firmation that emergency fire pump including factory condition and pump is building required ed pressure :bar AINS, HYDRANTS, HOSES, NOZZLES AND APP on of fire main (no soft patches or doublers) tors, spanners, relief valves and international sho NESS OF FIRE HYDRANTS, HOSES ose complete with couplings, nozzle (dual-purpos BLE EXTINGUISHERS AND FOAM APPLICATO nation that portable fire extinguishers correspond en examined were in good condition, fully charge CHARGES	g prime mover and priming water pressure and two jets of w LICATORS together with flanges and val- re connection. See nozzles where applicable) and DRS d to the fire control plan w.r.t. re ed and ready for use.	arrangements, gauges are water simultaneously. ves, hydrants, hoses, nozz d tools kept ready for use. number, type and location a			
tanka tanka Condition satis Testa Condition pplicat READIN Each ho PORTA Confirm hat who SPARE Availab FIRE Al t. Exam	ers). firmation that emergency fire pump including factory condition and pump is building required ed pressure :bar AINS, HYDRANTS, HOSES, NOZZLES AND APP on of fire main (no soft patches or doublers) tors, spanners, relief valves and international sho NESS OF FIRE HYDRANTS, HOSES ose complete with couplings, nozzle (dual-purpos BLE EXTINGUISHERS AND FOAM APPLICATO nation that portable fire extinguishers correspond en examined were in good condition, fully charge CHARGES bility of spare charge/s for each portable extinguish ND/OR SMOKE DETECTION SYSTEM	g prime mover and priming water pressure and two jets of w LICATORS together with flanges and val- re connection. See nozzles where applicable) and DRS d to the fire control plan w.r.t. re ed and ready for use.	arrangements, gauges are water simultaneously. ves, hydrants, hoses, nozz d tools kept ready for use. number, type and location a nguishers of the same type.			
tanka tanka Conditional condit	ers). firmation that emergency fire pump including factory condition and pump is building required ed pressure :bar AINS, HYDRANTS, HOSES, NOZZLES AND APP on of fire main (no soft patches or doublers) tors, spanners, relief valves and international sho NESS OF FIRE HYDRANTS, HOSES ose complete with couplings, nozzle (dual-purpos BLE EXTINGUISHERS AND FOAM APPLICATO nation that portable fire extinguishers correspond en examined were in good condition, fully charge CHARGES bility of spare charge/s for each portable extinguish ND/OR SMOKE DETECTION SYSTEM nine for proper functioning and possible testing le extraction smoke detection system. irmation that maintenance as recommended by r cturer's instructions for the system.	g prime mover and priming water pressure and two jets of v LICATORS together with flanges and val- re connection. (a) (a) (b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c	arrangements, gauges are water simultaneously. ves, hydrants, hoses, nozz d tools kept ready for use. number, type and location a nguishers of the same type. on and alarm system and a ten and spares available as			
tanko tanko c. Con: satis Testo FIREM/ Condition pplicat READIN Each ho PORTA Confirm hat who SPARE Availab FIRE Al t. Exan samplo. Confi nanufao FIXED 1	ers). firmation that emergency fire pump including factory condition and pump is building required ed pressure :bar AINS, HYDRANTS, HOSES, NOZZLES AND APP on of fire main (no soft patches or doublers) tors, spanners, relief valves and international sho NESS OF FIRE HYDRANTS, HOSES ose complete with couplings, nozzle (dual-purpos BLE EXTINGUISHERS AND FOAM APPLICATO nation that portable fire extinguishers correspondent en examined were in good condition, fully charge CHARGES bility of spare charge/s for each portable extinguistics ND/OR SMOKE DETECTION SYSTEM nine for proper functioning and possible testing le extraction smoke detection system. Firmation that maintenance as recommended by recurre's instructions for the system. FIRE FIGHTING SYSTEM (MACHINERY SPACE)	g prime mover and priming water pressure and two jets of v LICATORS together with flanges and val- re connection. The nozzles where applicable) and DRS d to the fire control plan w.r.t. red and ready for use. Sher or additional portable extin g as feasible any fire detection nanufacturer has been undertak E, PAINT LOCKER, DEEP FAT	arrangements, gauges are water simultaneously. ves, hydrants, hoses, nozz d tools kept ready for use. number, type and location a nguishers of the same type. on and alarm system and a ten and spares available as COOKING ETC.)			
tanka tanka c. Coni satis Testa Condition pplicat READIN Each ho PORTA Confirm hat who SPARE Availab FIRE Al t. Exan samplo c. Conf nanufac TIXED 1) Exan	ers). firmation that emergency fire pump including factory condition and pump is building required ed pressure :bar AINS, HYDRANTS, HOSES, NOZZLES AND APP on of fire main (no soft patches or doublers) tors, spanners, relief valves and international sho NESS OF FIRE HYDRANTS, HOSES ose complete with couplings, nozzle (dual-purpos BLE EXTINGUISHERS AND FOAM APPLICATO nation that portable fire extinguishers correspond en examined were in good condition, fully charge CHARGES bility of spare charge/s for each portable extinguist ND/OR SMOKE DETECTION SYSTEM nine for proper functioning and possible testing le extraction smoke detection system. Firmation that maintenance as recommended by r cturer's instructions for the system. FIRE FIGHTING SYSTEM (MACHINERY SPACE) nination of fixed firefighting system controls, p	g prime mover and priming water pressure and two jets of v LICATORS together with flanges and val- re connection. The nozzles where applicable) and DRS d to the fire control plan w.r.t. red and ready for use. Sher or additional portable extin- g as feasible any fire detection nanufacturer has been undertak E, PAINT LOCKER, DEEP FAT piping, instructions and markin	arrangements, gauges are water simultaneously. ves, hydrants, hoses, nozz d tools kept ready for use. number, type and location a nguishers of the same type. on and alarm system and a ten and spares available as COOKING ETC.)			
tanka tanka Conditional satis Testo FIREMA Conditional policat READIN Each ho PORTA Confirm hat who PORTA Confirm hat who PARE Availab FIRE Al a. Exan samplo. Confirm nanufac FIXED 1) Exan proper r i) Verimead dis ii) Exa applicat	ers). firmation that emergency fire pump including factory condition and pump is building required ed pressure :bar AINS, HYDRANTS, HOSES, NOZZLES AND APP on of fire main (no soft patches or doublers) tors, spanners, relief valves and international sho NESS OF FIRE HYDRANTS, HOSES ose complete with couplings, nozzle (dual-purpos BLE EXTINGUISHERS AND FOAM APPLICATO nation that portable fire extinguishers correspondent en examined were in good condition, fully charge CHARGES bility of spare charge/s for each portable extinguistic ND/OR SMOKE DETECTION SYSTEM nine for proper functioning and possible testing le extraction smoke detection system. FIRE FIGHTING SYSTEM (MACHINERY SPACI nination of fixed firefighting system controls, p maintenance and servicing including date of last fication with regard to correct positioning (for scharge valves for fixed firefighting CO2 system mination of fixed carbon dioxide fire-extinguis bel are provided with two separate controls, one	g prime mover and priming water pressure and two jets of v LICATORS together with flanges and val- re connection. e nozzles where applicable) and DRS d to the fire control plan w.r.t. of ed and ready for use. sher or additional portable extin g as feasible any fire detection nanufacturer has been undertak E, PAINT LOCKER, DEEP FAT piping, instructions and markin systems tests. in service condition) of safety are in accordance with manufa hing systems for the protection e for discharging the gas from	arrangements, gauges are water simultaneously. ves, hydrants, hoses, nozz d tools kept ready for use. number, type and location a nguishers of the same type. on and alarm system and a ten and spares available as COOKING ETC.) ng. Checking for evidence pins, where used on cylin cture's instruction manual. n of machinery spaces, wh			
tanka tanka Conditionation satis Testo FIREMA Conditionation PORTA Confirm hat who SPARE Availab FIRE Al a. Exan samplo. Confirm nanufao FIRE Al b. Confirm nanufao FIRE Al a. Exan samplo. Confirm nanufao FIXED I) Exan proper r i) Verimead dis ii) Exa applicat hem loo	ers). firmation that emergency fire pump including factory condition and pump is building required ed pressure :bar AINS, HYDRANTS, HOSES, NOZZLES AND APP on of fire main (no soft patches or doublers) tors, spanners, relief valves and international sho NESS OF FIRE HYDRANTS, HOSES use complete with couplings, nozzle (dual-purpose BLE EXTINGUISHERS AND FOAM APPLICATO nation that portable fire extinguishers correspondent en examined were in good condition, fully charge CHARGES bility of spare charge/s for each portable extinguish ND/OR SMOKE DETECTION SYSTEM nine for proper functioning and possible testing le extraction smoke detection system. FIRE FIGHTING SYSTEM (MACHINERY SPACI nination of fixed firefighting system controls, p maintenance and servicing including date of last fication with regard to correct positioning (for scharge valves for fixed firefighting CO2 system mination of fixed carbon dioxide fire-extinguis	g prime mover and priming water pressure and two jets of v LICATORS together with flanges and val- re connection. enozzles where applicable) and DRS d to the fire control plan w.r.t. in ed and ready for use. sher or additional portable extin g as feasible any fire detection manufacturer has been undertak E, PAINT LOCKER, DEEP FAT piping, instructions and markin systems tests. in service condition) of safety are in accordance with manufa hing systems for the protection e for discharging the gas from articular space.	arrangements, gauges are water simultaneously. ves, hydrants, hoses, nozz d tools kept ready for use. number, type and location a nguishers of the same type. on and alarm system and a ten and spares available as COOKING ETC.) ng. Checking for evidence pins, where used on cylin cture's instruction manual. n of machinery spaces, wh the storage container, each			

- When examined found to be satisfactory and/or examined/tested satisfactory and/or confirmed arrangements exist in satisfactory condition. No 1. repairs considered necessary this time.
- Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or 2. confirmed arrangements exist in satisfactory condition.
 Repairs now recommended and remain outstanding.
- 4. Opportunity to examine/test was not provided this time. Remains outstanding.

STRUCTURAL FIRE PROTECTION AND FIRE DAMPERS

Confirming, as far as practicable, that no changes have been made in the structural fire protection, examining any manual and automatic fire doors and proving their operation.

Testing the fire dampers of ventilation ducts and the means of closing the main inlets and outlets of all ventilation systems and testing the means of stopping power ventilation systems from outside the space served.

REMOTE STOPPING OF FANS, OIL PUMPS, ETC

Verify that the remote controls for stopping fans and machinery and shutting off fuel supplies in machinery spaces are in working order.

The stopping of ventilation and boiler forced and induced draft fans and the stopping of oil fuel and other pumps that discharge flammable liquids.

CLOSING ARRANGEMENTS FOR SKYLIGHTS, FLAPS ETC

Examination of closing arrangements of ventilators, funnel annular spaces, skylights, doorways and tunnel where applicable, including condition of operating mechanism e.g. wire ropes, hydraulic piping etc.

REMOTE CLOSING OF VALVES

- a. Examination of the arrangements for oil fuel, lubricating oil and other flammable oils and testing the remote closing of valves for oil fuel, lubricating oil and other flammable oils, and the operation of the remote means of closing the valves on the tanks contain oil fuel, lubricating oil and other flammable oils.
- b. Confirmation that quick closing valves are in satisfactory condition and no valve is isolated/disconnected and operating instructions are displayed.

FIREMAN'S OUTFITS & EEBDS

Confirmation that the fire fighters' outfits including its self-contained compressed air breathing apparatus and emergency escape breathing devices (EEBDs) are complete and in good condition and that the cylinders, including the spare cylinders, of any required self-contained breathing apparatus are suitably charged and that on board means of recharging apparatus cylinders used during drills or a suitable number of spare cylinders to replace those used are provided and provision of two-way portable radiotelephone apparatus of an explosion proof type or intrinsically safe.

WATER MIST LANCE

Examining the water mist lance and as appropriate, the mobile water monitors and all necessary hoses, fittings and required fixing hardware.

(Note: Applicable for ships designed to carry containers on or above weather deck, as applicable.)

MEANS OF ESCAPE

a. Confirmation that the means of escape from accommodation, machinery and other spaces are satisfactory.

b. Confirmation that opening of escape doors are in the way of direction of escape, handrails are provided in the corridors that are being used as escape routes and none of the doors along any designated escape routes require keys to unlock them when moving in the direction of escape.

GASEOUS FUEL FOR DOMESTIC PURPOSE

Examining the arrangements for gaseous fuel for domestic purposes.

CARGO SPACE

The operation of the means of control provided for closing the various openings.

GENERAL

HOUSE KEEPING

i) Verification that general housekeeping/cleanliness in engine room, on deck, accommodation, hospital, galley, wash basins and toilets are satisfactory.

ii) Confirmation that no loose drums and no heavy items without securing/lashing on deck.

iii) Confirmation that Spare anchor where provided, its lashing bracket in good condition.

FLAG SPECIFIC REQUIREMENTS

Confirmation that flag specific requirements/instructions, if any are complied with.

Please Provide details in Remark section.

H.O. INSTRUCTIONS

Confirmation that H.O. Instructions pertaining to this survey if any communicated separately, have been compiled with. Please Provide details in Remark section.

Condition to be reported using number code as follows:

- 1. When examined found to be satisfactory and/or examined/tested satisfactory and/or confirmed arrangements exist in satisfactory condition. No repairs considered necessary this time.
- 2. Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or confirmed arrangements exist in satisfactory condition.
- B. Repairs now recommended and remain outstanding.
- 4. Opportunity to examine/test was not provided this time. Remains outstanding.

SURVEY UNDERTAKEN ON BEHALF OF OTHER SOCIETY

For surveys on behalf of other society, confirmation that authorization, survey status and additional survey requirements if any are available and requirement related to reporting, endorsement of certificate, communication have been followed.

OVERDUE SURVEY

Confirmation that H.O. authorization is available for dealing with overdue surveys.

(Note: For dealing with overdue statutory surveys held together with Class surveys, Flag Administration authorization is required, details are to be provided in "Remarks")

REINSTATEMENT OF CLASS

Where the vessel was attended during suspension period, reference of relevant marine miscellaneous reports are provided in "Remarks" section which have been taken into account towards reinstatement of class.

SURVEY HELD BY OTHER SOCIETY ON BEHALF OF IRS

Confirmation that on board records verified for any survey held by other society on behalf of IRS (details to be included in "Remarks").

Where survey undertaken by other society on behalf of IRS, survey status updated with relevant information and a confirmatory survey carried out and found to be satisfactory.

REVIEW OF PORT STATE AND FLAG STATE INSPECTION REPORTS

Confirmation that reports of inspection by port state and flag state since last survey reviewed. Repairs/corrective action taken towards the deficiencies examined. Repairs to outstanding reported using Form "Cert-PSC".

Where the vessel was detained, a general examination was carried out as per Flag instruction and as required by survey procedure D-01 in consultation with H.O.

SURVEY ARRANGEMENTS

Verification of preparation for survey, means of access, safety arrangements for the safe and efficient conduct of the survey.

CALLIBRATION STATUS OF MEASURING AND TESTING EQUIPMENT

Verification of calibration status of measuring and testing equipment used for survey.

REMOTE INSPECTION TECHNIQUES

Confirmation that an inspection plan for the use of remote inspection techniques including any confirmatory survey/close-up survey/thickness measurements is submitted to H.O. and reviewed for acceptance prior commencement of survey.

Confirmation that risk assessment undertaken to identify any hazards, to assess the likelihood of an incident occurring and to establish control measures to minimize the risk so that mitigating measures as required are put in place for safe conduct of survey using the remote inspection technique.

Confirmation that a pre-meeting held between all parties i.e. surveyor, service supplier, ship owner's representatives in order to confirm planned arrangements as per inspection plan are in place so as to ensure safe and efficient conduct of the inspection. The equipment, procedure for observing, two-way communication between surveyor and RIT operator, data presentation including pictorial representation and reporting the surveys using RIT discussed and agreed with the parties prior to the RIT survey, and equipment set-up, calibrated prior the inspection.

When the remote inspection technique is used for a close-up survey, confirmation that such remote inspection technique is also able to carry out the required thickness measurements.

Where remote inspection technique is not able to carry out the required thickness measurements, confirmation that means of access for the corresponding thickness measurements provided. Confirmatory surveys/close up surveys including thickness measurement carried out as required at selected locations to verify the results of the remote inspection technique.

If the RIT reveals damage or deterioration that requires attention, confirmation that traditional survey undertaken without the use of a RIT. (Details to be provided in "Remarks")

CHANGES TO EQUIPMENT/SHIP PARTICULARS/LIST OF SURVEYABLE ITEMS

Changes to equipment/ship particulars/list of surveyable items reported using corresponding FE forms.

ADDITION/SUSPENSION/DELETION OF CLASS NOTATION

For any request for additional class notation where plan approval is required, Head Office authorization has been received. Separate reporting done using relevant checklists for class notations assigned to the vessel. Class certificate has been amended to reflect the amended class notation.

(Note: Details regarding addition/suspension/deletion of class notation is to be included under "Remarks")

Condition to be reported using number code as follows:

- 1. When examined found to be satisfactory and/or examined/tested satisfactory and/or confirmed arrangements exist in satisfactory condition. No repairs considered necessary this time.
- 2. Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or confirmed arrangements exist in satisfactory condition.
- 3. Repairs now recommended and remain outstanding.
- 4. Opportunity to examine/test was not provided this time. Remains outstanding.

PLAN APPROVAL COMMENTS

Relevant plan approval comments if any closed out in E-Plan arena.

ADDITIONAL REQUIREMENTS TOWARDS CLASS INTERMEDIATE SURVEY

APPROVED SURVEY PROGRAM

Confirmation of availability of approved survey program for the survey on board.

(Note: Applicable for vessels over 10years of age)

SURVEY PLANNING MEETING

Confirmation that survey planning meeting held between the attending surveyor(s), the owner's representative in attendance and where involved, the thickness measurement company representative and the Master of the ship or an appropriately qualified representative appointed by the Master or Company for the purpose to ascertain that all the arrangements envisaged in the survey programme are in place, so as to ensure the safe and efficient conduct of the survey work to be carried out.

CONTINUED COMPLIANCE WITH UR 19

Confirmation that thickness measurement and subsequent repairs/reinforcement required has been completed and vessel continues to comply with IACS UR S19 with respect to initial approval calculation/document for vertical corrugated aft transverse watertight bulkhead of fore most cargo hold for vessels subject to this requirement.

CONTINUED COMPLIANCE WITH UR 31

Confirmation that thickness measurement and subsequent repairs/reinforcement required has been completed and vessel continues to comply with IACS UR S31 with respect to initial approval calculation/document for side shell frames and brackets of cargo holds for vessels subject to this requirement

PIPING SYSTEM

(This section is applicable where the intermediate survey is equivalent to the previous special survey) Examination of all piping systems within Cargo Holds, Ballast Tanks incl. Double Bottom tanks, Fuel Oil Tanks, Pipe tunnels, Cofferdams and Void Spaces bounding cargo holds and operational testing to working pressure to confirm that the tightness and condition are satisfactory.

CLOSE-UP/OVERALL EXAMINATION OF CARGO HATCH COVERS AND COAMINGS INCL. OPERATION OF HATCH COVERS

(This section is applicable where the intermediate survey is equivalent to the previous special survey) i) Examination of all cargo hatch covers and coamings including their closing appliances, stowage, fit & operation (IRS Rules) for satisfactory condition.

ii) Confirmation that all mechanically operated hatch covers have been checked for operation and effectiveness of sealing arrangement and found to be satisfactory.

iii) Verification for continued compliance with IACS UR S30 for Cargo Hatch cover securing arrangements and stoppers for bulk carriers constructed before 1st January 2004 and not built in accordance with UR S21 (for No.1 and No.2 Cargo Hold Hatch).

EXAMINATION OF TANKS, SPACES AND THICKNESS MEASUREMENT

Confirmation that internal examination of tanks, spaces including testing and thickness measurements carried out satisfactorily as per the rule requirements and reported separately.

Examination of ballast tanks included examination of the condition of the corrosion prevention system in these spaces and found to be satisfactory.

Where special consideration is allowed as per the survey procedure and/or Main Rules Part 1, Chapter 2, the extent of thickness measurements is reduced, the special consideration is reported under "Remarks".

In case examination of tanks, spaces and thickness measurements are partly carried out, the extent of examination, thickness measurement carried out or pending is reflected in the survey status.

Confirmation that diminution criteria of other class society (under the special survey of which the vessel was built) is adopted for thickness measurement. (Details to be provided in "Remarks" section)

WATER INGRESSDETECTION AND ALARM SYSTEM

(This section is applicable where the intermediate survey is equivalent to the previous special survey) For ships complying with the requirements of SOLAS XII/12 for hold, ballast and dry space, confirmation that examination and a test, of the water ingress detection system and their alarms carried out and found to be satisfactory.

ADDITIONAL REQUIREMENTS TOWARDS SPECIAL SURVEY

APPROVED SURVEY PROGRAM

Confirmation of availability of approved survey program for the survey on board.

Condition to be reported using number code as follows:

- 1. When examined found to be satisfactory and/or examined/tested satisfactory and/or confirmed arrangements exist in satisfactory condition. No repairs considered necessary this time.
- 2. Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or confirmed arrangements exist in satisfactory condition.
- . Repairs now recommended and remain outstanding.

^{4.} Opportunity to examine/test was not provided this time. Remains outstanding.

SURVEY PLANNING MEETING

Confirmation that survey planning meeting held between the attending surveyor(s), the owner's representative in attendance and where involved, the thickness measurement company representative and the Master of the ship or an appropriately qualified representative appointed by the Master or Company for the purpose to ascertain that all the arrangements envisaged in the survey programme are in place, so as to ensure the safe and efficient conduct of the survey work to be carried out.

CLOSE-UP/OVERALL EXAMINATION OF CARGO HATCH COVERS AND COAMINGS INCL. OPERATION OF HATCH COVERS

i) Examination of all cargo hatch covers and coamings including their closing appliances, stowage, fit & operation (IRS Rules) for satisfactory condition.

ii) Confirmation that all mechanically operated hatch covers have been checked for operation and effectiveness of sealing arrangement and found to be satisfactory.

iii) Verification for continued compliance with IACS UR S30 for Cargo Hatch cover securing arrangements and stoppers for bulk carriers constructed before 1st January 2004 and not built in accordance with UR S21 (for No.1 and No.2 Cargo Hold Hatch).

EXAMINATION OF TANKS, SPACES AND THICKNESS MEASUREMENT

Confirmation that internal examination of tanks, spaces including testing and thickness measurements carried out satisfactorily as per the rule requirements and reported separately.

Examination of ballast tanks included examination of the condition of the corrosion prevention system in these spaces and found to be satisfactory.

Where special consideration is allowed as per the survey procedure and/or Main Rules Part 1, Chapter 2, the extent of thickness measurements is reduced, the special consideration is reported under "Remarks".

In case examination of tanks, spaces and thickness measurements are partly carried out, the extent of examination, thickness measurement carried out or pending is reflected in the survey status.

Confirmation that diminution criteria of other class society (under the special survey of which the vessel was built) is adopted for thickness measurement. (Details to be provided in "Remarks" section)

CONTINUED COMPLIANCE WITH UR 19

Confirmation that thickness measurement and subsequent repairs/reinforcement required has been completed and vessel continues to comply with IACS UR S19 with respect to initial approval calculation/document for vertical corrugated aft transverse watertight bulkhead of fore most cargo hold for vessels subject to this requirement.

CONTINUED COMPLIANCE WITH UR 31

Confirmation that thickness measurement and subsequent repairs/reinforcement required has been completed and vessel continues to comply with IACS UR S31 with respect to initial approval calculation/document for side shell frames and brackets of cargo hold for vessels subject to this requirement

MOORING ROPES AND TOW LINES

Confirmation that sufficient mooring ropes and tow lines as required by rules are provided onboard.

AIR PIPES

Internal Examination of Automatic air pipe heads as required by IRS Rules, to confirm these are maintained in satisfactory condition.

LONGITUDINAL STRENGTH EVALUATION FOR CSR BULK CARRIERS

(This section is applicable for CSR Bulk Carriers and during special surveys carried out after the ship reached 15 years of age or during the special survey No.3, if this is carried out before the ship reaches 15 years). Confirmation that the ship's longitudinal strength evaluated by using the thickness of structural members measured, renewed and reinforced, as appropriate, in accordance with the criteria for longitudinal strength of the ship's hull girder for CSR bulk carriers was considered acceptable.

(The final result of evaluation of the ship's longitudinal strength required above after renewal or reinforcement work of structural members, if carried out as a result of initial evaluation, is to be reported as a part of the Executive Hull Summary.)

MEANS OF EMBARKATION AND DISEMBARKATION

Confirmation that accommodation ladders, gangways and its winches incl. brake system operationally tested with specified maximum operation load in accordance with IRS and found to be satisfactory.

WATER INGRESS DETECTION AND ALARM SYSTEM

For ships complying with the requirements of SOLAS XII/12 for hold, ballast and dry space water level detectors, an examination and a test of the water ingress detection systems and of their alarms to confirm these are in satisfactory

Condition to be reported using number code as follows:

- 1. When examined found to be satisfactory and/or examined/tested satisfactory and/or confirmed arrangements exist in satisfactory condition. No repairs considered necessary this time.
- 2. Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or confirmed arrangements exist in satisfactory condition.
- . Repairs now recommended and remain outstanding.
- 4. Opportunity to examine/test was not provided this time. Remains outstanding.

condition.

PIPING SYSTEM

Examination of all piping systems within Cargo Holds, Ballast Tanks incl. Double Bottom tanks, Fuel Oil Tanks, Pipe tunnels, Cofferdams and Void Spaces bounding cargo holds including plating and framing, bilge and drain wells soundings, venting, pumping and drainage arrangements and operational testing to working pressure to confirm that the tightness and condition are satisfactory.

WATERTIGHT CABLE TRANSIT SEAL SYSTEMS

(Note: Applicable for all vessels contracted for construction on or after 1st July 2021)

i) Examination of all cable transit seal systems for their satisfactory condition and review of the cable transit seal systems register to confirm that it being maintained.

ii) Confirmation that where any disruption to the cable transits or installation of new cable transits carried out onboard from last special survey, records are reviewed and examination carried out for the satisfactory condition of those transits.

Confirmation that the results are recorded in the Register against each of those cable transits.

(Note: Entries that were reviewed and examined during previous annual survey may be excluded)

iii) Confirmation that the Special Survey is recorded in the Register.

(Note: A single record entry will be sufficient to record the survey of all transits.)

iv) Where the cable transits have been examined by an approved service supplier, review of the cable transit seal system register to confirm that it has been properly maintained by the owner and correctly endorsed by the service supplier.

ADDITIONAL REQUIREMENTS FOR CLASS ENTRY (EXISTING SHIP)

GENERAL

Authorization for undertaking the class entry survey including scope of survey, class notation to be assigned is available.

For transfer of class and dual classification cases confirmation that current classification survey status of the losing society/first society is available.

For any request for additional class notation where plan approval is required, Same has been undertaken in consultation of HOD (classification & certification). Include details under "Remarks".

Separate reporting done using relevant checklists for class notations assigned to the vessel.

GENERAL EXAMINATION OF ESSENTIAL MACHINERIES

Examination of oil fuel burning equipment of boiler, economizers and steam/steam generators under working conditions. The adjustment of safety valves of this equipment verified.

External examination of all pressure vessels including their associated piping and protective devices. Internal examination and hydraulic testing carried out satisfactorily as considered necessary.

(Note: Provide details under remark section where tests carried out.)

Examination of generator circuit breakers, preference tripping relays and generator prime mover governors including verification of insulation resistance, paralleling and load sharing for their satisfactory condition.

Examination of navigating lights and indicators for their working condition including verification of alternative sources of power.

Confirmation that following machinery and items have been dismantled and inspected for satisfactory condition. (Note: Details of items inspected undertaken are to be provided in below table.)

	Machinery/Items	Details
a.	Main Engine	
b.	Auxiliary Engine(s)	
с.	Pumps	
d.	Pressure Vessels (Air bottles)	
e.	Compressors	
f.	Any other machinery/item (please specify the same under "Details")	

Condition to be reported using number code as follows:

- 1. When examined found to be satisfactory and/or examined/tested satisfactory and/or confirmed arrangements exist in satisfactory condition. No repairs considered necessary this time.
- 2. Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or confirmed arrangements exist in satisfactory condition.
- 3. Repairs now recommended and remain outstanding.
- 4. Opportunity to examine/test was not provided this time. Remains outstanding.

Examination of following items under working conditions:

a. Bilge Pumps

b. Emergency Fire Pumps

c. Remote control for oil valves, oil fuel pumps, lubricating oil pumps, forced draught fans

Examination of recirculating and ice clearing arrangements, if any for satisfactory condition.

Examination of main and all auxiliary machinery necessary for operation of the vessel at sea together with their essential controls to confirm satisfactory working condition.

Examination and testing of steering gear under working condition including testing of alternate means of steering for satisfactory working.

Verification of initial start arrangements for satisfactory condition.

Confirmation that a short sea trial held satisfactorily.

(Note: 1. Mandatory where the vessel was laid up for a long period.

2. For class entry of non-compliant vessel subject to IACS PR 1D, sea trial to be undertaken in accordance with approved protocol as per survey procedure B-03)

Any class notation included in H. O. authorization but not assigned.

(Note: Include explanation included in "Remarks".)

AVAILABILITY OF PLANS/DOCUMENTS

All relevant plans/ documents are available. If not appropriate actions initiated in consultation with Head Office.

(Note: (i) For class entry involving IACS PR 1D, plans/documents listed in Part 1, Chapter 1 Section 3.2.1 to 3.2.5 of the IRS Rules are to be appraised.

(ii)Plans/documents as listed in survey procedure B-03 Annexure 2 are to be submitted to head office.)

Shipboard arrangement verified against plans/documents and confirmation that no alteration/modification is done to the vessel.

Where plans/documents not available, confirmation that technical data collected in lieu of specific plan/document and sent to Head Office (HOD (PAC-Existing Ships) and HOD (Classification & Certification)).

THICKNESS MEASUREMENTS

Where class entry survey is to be credited as a periodical survey for maintenance of class thickness measurements undertaken by the losing society carried out within the applicable survey window of the periodical survey being credited and accepted based on satisfactory review for compliance with the applicable survey requirements, and confirmatory gauging now undertaken as reported.

(Note: Copy of TM to be uploaded)

Where class entry survey is not to be credited as a periodical survey for maintenance of class thickness measurements undertaken by the losing society carried out within 15 months prior to completion of class entry survey (when it is in the scope of a Special Survey)/within 18 months prior to completion of class entry survey (when it is in the scope of an Intermediate Survey)* and accepted based on satisfactory review for compliance with the applicable survey requirements, and confirmatory gauging now undertaken as reported.

(Note: Copy of TM to be uploaded)

EXAMINATION OF BALLAST TANKS AND CARGO SPACES

Examination of ballast tanks and cargo spaces undertaken and are reported separately.

TANKS TESTING

Testing of ballast tanks undertaken as reported separately.

ANCHORS AND ANCHOR CHAIN CABLES

Confirmation that anchors examined and chain cables ranged and gauged and found to be satisfactory.

OVERDUE SURVEY AND CONDIIONS OF CLASS

Confirmation that (i) all overdue surveys and (ii) all overdue conditions of class previously issued against the vessel as specified to the Owner by the losing Society, have been dealt with satisfactorily.

(Note: Applicable for vessels less than 15 years of age)

Confirmation that (i) all overdue surveys and (ii) all overdue conditions of class previously issued against the vessel have been dealt with satisfactorily by the losing society.

(Note: Applicable for vessels of 15years of age and over)

Condition to be reported using number code as follows:

- 1. When examined found to be satisfactory and/or examined/tested satisfactory and/or confirmed arrangements exist in satisfactory condition. No repairs considered necessary this time.
- 2. Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or confirmed arrangements exist in satisfactory condition.
- 3. Repairs now recommended and remain outstanding.

^{4.} Opportunity to examine/test was not provided this time. Remains outstanding.

OUTSTANDING CONDITION OF CLASS

Confirmation that all outstanding conditions of class issued by the losing society which have not been dealt with during class entry have been reflected in the survey status.

(Note: Details of outstanding conditions of class dealt with at the time of class entry are to be reported separately)

MATERIAL TESTING

Confirmation that material used for construction of the vessel meet Rule requirements and confirmed through material testing as required by survey procedure B-03.

(Note: (i)Material testing is required to be carried out at accredited laboratory (accredited to ISO 17025 or equivalent) or at a laboratory approved by the respective Flag Administration.

(ii) Applicable to class entry of non-compliant vessel subject to IACS PR 1D)

NON-DESTRUCTIVE TESTING

Confirmation that NDT of weld joints undertaken as required by survey procedure B-03.

(Note: Applicable to class entry of non-compliant vessel subject to IACS PR 1D)

HYDRAULIC TEST

Confirmation that hydraulic testing of pressure vessel and piping system carried out in accordance with applicable class rules as per survey procedure B-03.

(Note: Applicable to class entry of non-compliant vessel subject to IACS PR 1D)

COMPLIANCE TO RETROACTIVE RULE REQUIREMENTS

Confirmation that vessel is in compliance with retroactive Rule requirements which are applicable to the vessel at the time of class entry

(Note: Applicable to class entry of non-compliant vessel subject to IACS PR 1D)

INSTRUCTION FROM FLAG ADMINISTRATION

Confirmation that specific instruction from flag if any is taken into account.

CHANGE OF FLAG/CHANGE OF CERTIFICATION SURVEY (EXISTING SHIP)

Valid Permanent/ Provisional Registry certificate is available as issued by gaining flag/flag for which certification is being done.

IRS has authorization to carry out surveys on behalf of the flag. HO authorization including scope of survey, requirement for approval of statutory documents on behalf of the flag has been received.

Statutory certificates, supplements & documents issued on behalf of previous flag/RO are available.

Exemptions, where applicable, have been issued by the gaining flag / flag for which certification is being done.

Information on additional flag requirements, if any are taken into account.

All relevant drawings, documents etc. are available. If not, appropriate actions initiated.

Plans and documents requiring approval on behalf of gaining flag have been approved.

Confirmation that mandatory certificate, documents required to be carried on board are available.

(Note: Refer Instruction to Surveyors (Statutory) D-05 and Flag instruction)

Confirmation that statutory documents/plans onboard are in the language as required by applicable conventions, codes and confirming flag specific requirements.

Confirmation that marking and carving as required by flag has been done on the vessel.

Confirmation that new flag, port of registry and ship's name are indicated, as applicable, on life boats, life rafts, life buoys, statutory documents as applicable.

Confirmation that vessel is in compliance with new statutory requirements due to changes to statutory regulations as applicable to the vessel on the date of survey.

STATUS OF SURVEY AND CERTIFICATE

Confirmation that the Annual Survey/Intermediate Survey/Special Survey* completed satisfactorily.

General examination of the vessel carried out satisfactorily towards [postponement of special survey/for granting voyage permission/towards class entry/towards condition improvement program/(specify)]* with the scope of Annual survey/ Intermediate Survey/Special Survey* relevant to the age and type of the vessel as per Rules.

(Note: (i)Authorisation reference received from head office/flag Administration are to be provided under "Remarks" (ii)Further survey scope covered for postponement survey are to be confirmed by indicating under "Remarks")

Condition to be reported using number code as follows:

- 1. When examined found to be satisfactory and/or examined/tested satisfactory and/or confirmed arrangements exist in satisfactory condition. No repairs considered necessary this time.
- 2. Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or confirmed arrangements exist in satisfactory condition.
- 3. Repairs now recommended and remain outstanding.

4. Opportunity to examine/test was not provided this time. Remains outstanding.

On satisfactory completion of the survey/examination* Full-Term Certificate issued/endorsed/extended/interim certificate issued/short term certificate issued*

(Note: Validity of the short-term certificates and other conditions based on which the certificate is issued are to be included in the "Remarks" section)

Confirmation that the Annual Survey/Intermediate Survey/Special survey* carried out partly as reported. Extent of survey/examination* carried out/pending* is reflected in the survey status.

(Note: Explanation for carrying out surveys partly may be included under "Remarks")

Annual Survey/Intermediate Survey/Special survey/General examination* could not be completed due to reason as provided under "Remarks" and the survey window having been expired it is recommended that the class of the vessel may be suspended. Extent of survey/examination carried out /pending is reflected in the survey status as additional information and pending repairs to deficiencies have been reflected in the survey status as condition of class.

The special survey has been preponed in consultation with the Flag Administration for alignment with statutory renewal surveys. A fresh date for special survey is recommended to be assigned.

The Annual/Intermediate* survey has been completed before the survey window at the request of the owner and the anniversary date is amended in the class certificate accordingly.

Condition to be reported using number code as follows:

^{1.} When examined found to be satisfactory and/or examined/tested satisfactory and/or confirmed arrangements exist in satisfactory condition. No repairs considered necessary this time.

Repairs now recommended and were carried out satisfactorily. After repairs found to be satisfactory and/or examined/ tested satisfactorily and/or confirmed arrangements exist in satisfactory condition.

^{8.} Repairs now recommended and remain outstanding.

^{4.} Opportunity to examine/test was not provided this time. Remains outstanding.